Head mounted Transmitter

General specification	Deviations list
Ref. TiXo 3 or equivalent	
Hart® / programmable temperature tansmitter	
Head mounting type	
Universal Input	
Output: 4/20mA (2-wires technologie)	
Power supply: 10 to 30 Vdc	
Galvanic isolation: 1500Vac	
Hart® protocole supported for configuration	
See datasheet of TiXo2 for more details	
TiXo3 = TiXo2 + Hart® Protocol	



Item	Tag number	Type		Qty.
All tags with note **H** of transmitter datasheets		TiXo 3	Or equivalent	30
All tags with note **H** of transmitter datasheets		Calibration TiXo	Tag + Range programmation + Test certificate 5 points	30

Din **R**ail Transmitter

General specification		Deviations list
Ref. TiXo 3 or equivalent		
Hart® / programmable temperature tansmitter		
Head mounting type		
Universal Input		
Output: 4/20mA (2-wires technologie)		
Power supply: 10 to 30 Vdc		
Galvanic isolation: 1500Vac		
Hart® protocole supported for configuration		
See datasheet of TiXo2 for more details		
TiXo3 = TiXo2 + Hart® Protocol		
Ref. ACCDIVTX01		
DIN mounting kit for TiXo		
Ref. Rail DIN		
Length: 1m		
without fixation		



Item	Tag number	Type		Qty.
All tags with note **R** of transmitter datasheets		TiXo3	Or equivalent	183
All tags with note **R** of transmitter datasheets		ACCDIVTX01		183
All tags with note **R** of transmitter datasheets		RAILDIN1M	Din Rail length calcul: 195(pcs) x 50(mm) = 9,8 meter	10
All tags with note **R** of transmitter datasheets		Calibration TiXo	Tag + Range programmation + Test certificate 5 points	183